

Application:

The SSL selector switches are suitable for

- used in zone 1, zone 2 and zone 21, zone 22 in hazardous locations
- use in conjunction with magnetic starters or contactors for remote control of motors.
- indoor, outdoor and corrosive locations.
- circuit control of motors.

Technical data:

Explosion Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079-1 or UL 60079-0/1
Marking for test	: Ex II2G
Degree of Protection	: IP54/65 (option) acc. To IEC 60529
Ambient Temp. (Ta)	: -20°C to + 55°C
Protection class for UL	: Class I, Division 1 or 2 Group. C, D
	: Class II, Division 1 or 2 Groups. E, F, G
	: Class III
Protection class for IEC	: Zone 1, 21 and Zone 2, 22
Conduit hub size	: 3/4" NPT

Specification:

Body and cover : Marine grade copper-free aluminum alloy
with polyester powder coated , RAL 7032 (Grey)

Options:

Silicone rubber on cover selector switches Type **R** for **IP66**

Rating:

Contact rating : 3A.. 220V.AC.
Rated insulation current : 10A..

Catalogue Number:

Number of contact	Diagram Left Center Right	Nameplate Marking	Cat.,No	
			Dead-end (1 hub)	Through-feed (2 hub)
2 - Positions				
1NO	 - 	OFF - NO	SSL 210	SSL 210H
2NO	 - 	OFF - NO	SSL 220	SSL 220H
2NO - 2NC	 - 	MAN. - AUTO	SSL 211	SSL 211H
3 - Positions				
2NO	  	MAN. - OFF - AUTO	SSL 320	SSL 320H
2NC	  	Specify	SSL 302	SSL 302H

