

HAMAI

BALL VALVES

(TYPE BBS)




WATER OIL & GAS

**BRASS BALL VALVES
REDUCED BORE, SCREWED END TYPE.**

SPECIAL FEATURES:

BRASS SCREWED END TYPE

- HAMAI type BBS Ball Valves are highly recommended for positive shut-off of water, oil, and gas control.
- Completely free from pin-hall and cracks.
- Compact design, quarter-turn operation and economical.



OPERATING CONDITION:

MAX. OPERATING PRESSURE: 20 kgf/cm² (300 psi)
RECOMMENDED FOR WATER, OIL AND GAS

NOTE:

1. ENDS AVAILABLE: SCREWED, BS NPT AND PT
2. BUTTERFLY AND WING SHAPE HANDLES ARE AVAILABLE (1/4 THRU 1/2 FOR BUTTERFLY, 3/4 THRU 2 FOR WING HANDLE)
3. DUE TO CONTINUOUS DEVELOPMENT OF VALVES, WE RESERVE THE RIGHT TO ALTER THE DIMENSIONS AND INFORMATION CONTAINED IN ALL OUR LITERATURE AS REQUIRED.

MATERIALS:

PART NO.	DESCRIPTION	MATERIAL
1	VALVE BODY	BRASS (C3771)
2	END CAP	BRASS (C3604)
3	BALL	BRASS CHROME PLATING
4	SEAT	TEFLON (PTFE)
5	STEM	BRASS (C3604)
6	HANDLE	SUS 430
7	GLAND WASHER	CARBON STEEL
8	A PACKING	TEFLON (PTFE)
9	B PACKING	TEFLON (PTFE)
10	CONICAL SPRING	SUS 304
11	SPRING WASHER	CARBON STEEL
12	NUT	SUS 400

DIMENSIONS:

SIZE	d	L	L1	(L2)	(H)	W	(W1)
BBS 1/4	5	40	19	60	31	17	19.5
BBS 3/8	7.5	44.5	21.7	80	40	21	24
BBS 1/2	9	54.5	26.5	80	42	26	30
BBS 3/4	12.5	61	30	100	51	32	37
BBS 1	16	75	36.5	100	55	41	47
BBS 1-1/4	21	80	41	150	66	48	55
BBS 1-1/2	24	84	43	150	69	54	62
BBS 2	32	102	52	150	75	67	77



HAMAI

HAMAI INDUSTRIES LIMITED.

5-22-13 NISHI-GOTANDA, SHINAGAWA-KU, TOKYO, 141 JAPAN
PHONE: (03) 3492-6655 FAX: (03) 3492-6660